

## A21, A22



**TECHNICAL FEATURES:**

- Machine body Ø360mm
- Side channel blower with three phase motor asynchronous
- Vacuum-meter to control the filter efficiency
- Electric cable 9m with CEE 2P+T plug
- Manual filter shaker on side
- Star filter of polyester cat. "L" - Ø360mm, 8 pockets for A21 model
- Star filter of polyester cat. "L" - Ø360mm, 12 pockets for A22 model
- Quick inlet Ø70mm
- Waste bin of 25 l with integrated handle and castors
- Rear castors Ø125mm, front castors Ø100mm with brake
- Painted version with trolley Ral 9005 (black), container and filter chamber Ral 9003 (white)
- X1 version with waste bin in stainless steel
- X2 version with waste bin and filter chamber in stainless steel
- X3 version all in stainless steel
- We recommend using accessories of Ø40mm

		A21	A22
Tension / Voltage	Volts	230-400V/50Hz	230-400V/50Hz
Power	Kw	1.1	1.5
Depression max	mbar max	250	250
Max working depression	mbar	200	200
Max air flow	m <sup>3</sup> /h	140	210
Primary filter surface	m <sup>2</sup>	0,70	1,14
Absolute filter surface	m <sup>2</sup>	1,20	1,20
Container capacity	Lt	25	25
Product inlet	mm	Ø70	Ø70
Noise level	DbA	65	67
Overall dimensions	Cm	47x61x118h	47x61x135h
Weight	Kg	55	60
Protection	IP	55	55